



LED DISPLAYS:ELS-40101A/B SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25°C)

Part No.	Emitted Color	Peak Wave Length	Epoxy Color	Surface Color	Common Electrode	$\Delta\lambda$ (nm)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
									Segment	Dot	Min	Max
ELS-40101AS	Red	620-630	White	Black	Cathode	10	20	60	9.0-10.0	1.8-2.0	82	92
ELS-40101AO	Orange	600-610	White	Black	Cathode	10	20	60	9.0-10.0	1.8-2.0	85	95
ELS-40101AY	Yellow	585-595	White	Black	Cathode	10	20	60	9.0-10.0	1.8-2.0	88	98
ELS-40101AG	Olivine	565-575	White	Black	Cathode	10	20	60	9.0-10.0	1.8-2.0	10	20
ELS-40101AGG	Emerald	515-525	White	Black	Cathode	10	20	60	13.0-14.0	2.6-2.8	215	225
ELS-40101AB	Blue	460-470	White	Black	Cathode	10	20	60	13.0-14.0	2.6-2.8	15	25
ELS-40101AW	White	-	-	Black	Cathode	-	20	60	13.0-14.0	2.6-2.8	-	-
ELS-40101BS	Red	620-630	White	Black	Anode	10	20	60	9.0-10.0	1.8-2.0	82	92
ELS-40101BO	Orange	600-610	White	Black	Anode	10	20	60	9.0-10.0	1.8-2.0	85	95
ELS-40101BY	Yellow	585-595	White	Black	Anode	10	20	60	9.0-10.0	1.8-2.0	88	98
ELS-40101BG	Olivine	565-575	White	Black	Anode	10	20	60	9.0-10.0	1.8-2.0	10	20
ELS-40101BGG	Emerald	515-525	White	Black	Anode	10	20	60	13.0-14.0	2.6-2.8	215	225
ELS-40101BB	Blue	460-470	White	Black	Anode	10	20	60	13.0-14.0	2.6-2.8	15	25
ELS-40101BW	White	-	-	Black	Anode	-	20	60	13.0-14.0	2.6-2.8	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

Reverse Voltage	Reverse Current (VR=5V)	Operating Temperature Range	Storage Temperature Range	Lead Soldering Temperature
5V	20 μ A	-35°C~+80°C	-45°C~+80°C	260°C For 3 Seconds

PACKAGE DIMENSION (Tolerance : ± 0.2 mm)

