



LED DISPLAYS:ELS-40101C/D SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25°C)

Part No.	Emitted Color	Peak Wave Length	Epoxy Color	Surface Color	Common Electrode	$\Delta\lambda$ (nm)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
									Segment	Dot	Min	Max
ELS-40101CS	Red	620-630	White	Black	Cathode	10	20	60	7.2-8.0	3.6-4.0	82	92
ELS-40101CO	Orange	600-610	White	Black	Cathode	10	20	60	7.2-8.0	3.6-4.0	85	95
ELS-40101CY	Yellow	585-595	White	Black	Cathode	10	20	60	7.2-8.0	3.6-4.0	88	98
ELS-40101CG	Olivine	565-575	White	Black	Cathode	10	20	60	7.2-8.0	3.6-4.0	10	20
ELS-40101CGG	Emerald	515-525	White	Black	Cathode	10	20	60	10.4-11.2	5.2-5.6	215	225
ELS-40101CB	Blue	460-470	White	Black	Cathode	10	20	60	10.4-11.2	5.2-5.6	15	25
ELS-40101CW	White	-	-	Black	Cathode	-	20	60	10.4-11.2	5.2-5.6	-	-
ELS-40101DS	Red	620-630	White	Black	Anode	10	20	60	7.2-8.0	3.6-4.0	82	92
ELS-40101DO	Orange	600-610	White	Black	Anode	10	20	60	7.2-8.0	3.6-4.0	85	95
ELS-40101DY	Yellow	585-595	White	Black	Anode	10	20	60	7.2-8.0	3.6-4.0	88	98
ELS-40101DG	Olivine	565-575	White	Black	Anode	10	20	60	7.2-8.0	3.6-4.0	10	20
ELS-40101DGG	Emerald	515-525	White	Black	Anode	10	20	60	10.4-11.2	5.2-5.6	215	225
ELS-40101DB	Blue	460-470	White	Black	Anode	10	20	60	10.4-11.2	5.2-5.6	15	25
ELS-40101DW	White	-	-	Black	Anode	-	20	60	10.4-11.2	5.2-5.6	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

Reverse Voltage	Reverse Current (VR=5V)	Operating Temperature Range	Storage Temperature Range	Lead Soldering Temperature
5V	20 $\mu$ A	-35°C ~ +80°C	-45°C ~ +80°C	260°C For 3 Seconds

PACKAGE DIMENSION (Tolerance :  $\pm 0.2$ mm)

