



LED DISPLAYS:ELC-5301 SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25°C)

Part No.	Emitted Color	Peak Wave Length	Epoxy Color	Surface Color	$\Delta\lambda$ (nm)	Pd (mW)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
									Min	Max	Min	Max
ELC-5301R	Red	620-630	White	Black	10	35	20	60	1.8	2.0	82	92
ELC-5301O	Orange	600-610	White	Black	10	35	20	60	1.8	2.0	85	95
ELC-5301Y	Yellow	585-595	White	Black	10	35	20	60	1.8	2.0	88	98
ELC-5301G	Olivine	565-575	White	Black	10	35	20	60	1.8	2.0	10	20
ELC-5301GG	Emerald	515-525	White	Black	10	55	20	60	2.6	2.8	215	225
ELC-5301B	Blue	460-470	White	Black	10	55	20	60	2.6	2.8	15	25
ELC-5301W	White	-	-	Black	-	55	20	60	2.6	2.8	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

Reverse Voltage	Reverse Current (VR=5V)	Operating Temperature Range	Storage Temperature Range	Lead Soldering Temperature
5V	20 μ A	-35°C ~ +80°C	-45°C ~ +80°C	260°C For 3 Seconds

PACKAGE DIMENSION (Tolerance : ± 0.2 mm)

