



LED DISPLAYS: ELD-4201C/D SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25°C)

Part No.	Emittd Color	PeakWave Length	Epoxy Color	Surface Color	Common Electrode	$\Delta\lambda$ (nm)	Pd (mW)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
										Min	Max	Min	Max
ELD-4201CS	Red	620-630	White	Black	Cathode	10	35	20	60	1.8	2.0	82	92
ELD-4201CO	Orange	600-610	White	Black	Cathode	10	35	20	60	1.8	2.0	85	95
ELD-4201CY	Yellow	585-595	White	Black	Cathode	10	35	20	60	1.8	2.0	88	98
ELD-4201CG	Olivine	565-575	White	Black	Cathode	10	35	20	60	1.8	2.0	10	20
ELD-4201CGG	Emerald	515-525	White	Black	Cathode	10	55	20	60	2.6	2.8	215	225
ELD-4201CB	Blue	460-470	White	Black	Cathode	10	55	20	60	2.6	2.8	15	25
ELD-4201CW	White	-	-	Black	Cathode	-	55	20	60	2.6	2.8	-	-
ELD-4201DS	Red	620-630	White	Black	Anode	10	35	20	60	1.8	2.0	82	92
ELD-4201DO	Orange	600-610	White	Black	Anode	10	35	20	60	1.8	2.0	85	95
ELD-4201DY	Yellow	585-595	White	Black	Anode	10	35	20	60	1.8	2.0	88	98
ELD-4201DG	Olivine	565-575	White	Black	Anode	10	35	20	60	1.8	2.0	10	20
ELD-4201DGG	Emerald	515-525	White	Black	Anode	10	55	20	60	2.6	2.8	215	225
ELD-4201DB	Blue	460-470	White	Black	Anode	10	55	20	60	2.6	2.8	15	25
ELD-4201DW	White	-	-	Black	Anode	-	55	20	60	2.6	2.8	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

Reverse Voltage	Reverse Current (VR=5V)	Operating Temperature Range	Storage Temperature Range	Lead Soldering Temperature
5V	20 μ A	-35°C ~ +80°C	-45°C ~ +80°C	260°C For 3 Seconds

PACKAGE DIMENSION (Tolerance : ± 0.2 mm)

